BUILT STRONG. BUILT LOCAL. BUILT TO PERFORM.

PRODUCT SPEC SHEET

RECTANGULAR ROLL-OFFS

Straight-wall roll-off containers from 10 to 50 yards, built for standard roll-off hoists. 10 gauge floor on 3″ channels, 12 gauge side walls and tubing top rails.

HAMBICKI PRODUCTS & CONTAINER SALES



BUILT IN PHOENIX, ARIZONA

STANDARD SPECIFICATIONS

- ✓ 10 Gauge Floor, Welded Solid Inside, Reinforced by 3" Structural Channels on 18" Centers
- ✓ 12 Gauge Side Walls, Overlapped, Welded Solid Inside, Outside Walls Stitched Weld, Reinforced by 3"x3"x3/16" Tubing Top Rails, With Reinforced V-Hits Every 12" Down the Sides, Horizontal Side Uprights with a Reinforced V-Hit to add Strength, Spaced Every 24" Down the Sides
- ✓ Standard Rail Width 36 ½ Cable, Standard Rail Width 37 ½" Hook Hoist
- ✓ Positive Self-Centering Stabilizing Two Longitudinal Guide Rails (6"x2"x3/16" Tubing)
- ✓ Interior and Bottom of Container Primed

SIZES

SIZE	DIMENSIONS
10 YD	12' L × 3½' H × 8' W
12 YD	14' L × 3½' H × 8' W
15 YD	16' L × 3½' H × 8' W
20 YD	22' L × 3½' H × 8' W

OPTIONAL ACCESSORIES



HOOK HOIST



SIDE PLATE



ROLLING LIDS



SEALED STEEL LIDS



DOUBLE REAR DOORS



SEALED INTERIOR WITH DRAIN PLUG

REQUEST A QUOTE

602-268-8708

www.hambickiproducts.com

Proudly built in Arizona, USA

Heavy-duty steel · Custom manufacturing · Nationwide shipping

DESIGNED. BUILT. DELIVERED. ON TIME. EVERY TIME.